

OXXE ULS No.2 Diesel

Descripción

OXXE ULS No.2 Diesel CARB compliant <15 ppm sulfur. Wax free. -75F pour point. Off-road red dye also available.

OXXE ULS No.2 Diesel Clear Specifications Sheet

TYPICAL PROPERTIES	ASTM Test Method	MIN	TYPICAL	MAX
API Gravity at 60 °F	D287		30	
Color	D1500		1.0	
Specific Gravity			0.8762	
Pounds per Gallon			7.296	
Flash Point, in °F, PMCC	D93	125	140	
Sulfur, PPM	D5453		6	15
Ash, wt. %	D482		< 0.01	0.01
Cloud Point, in °F	D2500		0	
Pour Point, in °F	D97		-75	
Ramsbottom Carbon Residue on 10% Dist. Residue, % Mass	D524		< 0.35	0.35
BS&W, vol. %	D1796/D2709		< 0.05	0.05
Cetane No.	D613	40	> 40	
Kinematic Viscosity mm/s at 40 °C	D445	1.9	3.8	4.1
Aromatics, Vol. Recovered	D5186		< 20	20
Distillation Temp in °F 90% Volume Recovered	D86	540	< 640	640
Copper Strip Corrosion Rating 3 H at 50 °C	D130		< NO.3	NO.3
Lubricity HFRR at 60 °C Micron, Max.	D6079/D7688		340	520
Conductivity, pS/m Min.	D2624/D4308	25	320	

OXXE ULS No.2 Diesel

OXXE ULS No.2 Diesel Clear Specifications Sheet

TYPICAL PROPERTIES	ASTM	MIN	TYPICAL	MAX
	Test Method			
API Gravity at 60 °F	D287		30	
Color	D1500		1.0	
Specific Gravity			0.8762	
Pounds per Gallon			7.296	
Flash Point, in °F, PMCC	D93	125	140	
Sulfur, PPM	D5453		6	15
Ash, wt. %	D482		< 0.01	0.01
Cloud Point, in °F	D2500		0	
Pour Point, in °F	D97		-75	
Ramsbottom Carbon Residue on 10% Dist. Residue, % Mass	D524		< 0.35	0.35
BS&W, vol. %	D1796/D2709		< 0.05	0.05
Cetane No.	D613	40	> 40	
Kinematic Viscosity mm/s at 40 °C	D445	1.9	3.8	4.1
Aromatics, Vol. Recovered	D5186-91		< 20	20
Distillation Temp in °F 90% Volume Recovered	D86	540	< 640	640
Copper Strip Corrosion Rating 3 H at 50 °C	D130		< NO.3	NO.3
Lubricity HFRR at 60 °C Micron, Max.	D6079/D7688		340	520
Conductivity, pS/m Min.	D2624/D4308	25	320	

Presentación

El producto está disponible en las siguientes presentaciones:

- Caja de 12 unidades por cuarto de galón.
- Caja de 6 unidades por galón.
- Garrafa de 5 galones.
- Tambores de 55 galones.
- Contenedores de 264 galones

OXXE ULS No.2 Diesel



ROYAL Petroleum Corporation C.I S.A.S

Zona Franca Industrial Km 1 vía Gaira. Planta 4F

Santa Marta, Colombia

Tel: (575) 4232258 – 3118109765

Email: royal@royalpetroleum.co

www.royalpetroleum.co