

# OXXENAP

## Descripción

**OXXENAP** Lubricating Base Oils, Insecticides, Explosives, Paints & Coatings, Pigments, Hydraulic Fluids, Industrial Lubricants, Metalworking Fluids, Pump Oil, Process Oil

## OXXENAP Series Specifications Sheet

TYPICAL PROPERTIES	ASTM	HYNAP				
	Test Method	N40HT	N60HT	N100HTS	2000	4000
Viscosity						
at 100 °F, SUS	<b>D2161</b>	40.8	60.2	120	1953	4140
at 210 °F, SUS		31.2	34.0	38.4	75.8	99
at 40 °C, cSt	<b>D445</b>	4.28	9.63	23.0	349.5	723
at 100 °C, cSt		1.53	2.31	3.58	13.93	19.27
API Gravity	<b>D287</b>	29.7	28.0	26.0	18.3	15.7
Specific Gravity at 60 °F	<b>D1250</b>	0.8778	0.8771	0.8984	0.9446	0.9613
Density, lb/gal, at 60 °F	<b>D1250</b>	7.309	7.387	7.481	7.866	8.005
Color	<b>D1500</b>	L0.5	L0.5	L1.5	L3.0	L4.0
Flash, COC, in °F	<b>D92</b>	260	280	345	440	455
Pour Point, in °F	<b>D97</b>	< -60	-50	-30	30	40
Aniline Point, in °F	<b>D611</b>	153	165	178	163	148
Refractive Index at 20 °C	<b>D1218</b>	1.4821	1.4819	1.4883	1.5229	1.5332
Neut. No., mg KOH/g	<b>D974</b>	< 0.05	< 0.05	< 0.05	0.07	0.12
Sulfur, w%	<b>D2622</b>	< 0.003	< 0.003	< 0.003	0.17	0.20
Clay-Gel Analysis	<b>D2007</b>					
w% Asphaltenes					0	0
w% Polar Compounds					10	11
w% Aromatics					42	51
w% Saturates					48	38
Carbon-Type Analysis	<b>D2140</b>					
% Ca		12	4	4	21	25
% Cn		44	54	52	37	37
% Cp		44	42	44	42	38

# OXKENAP

## **Presentación**

---

El producto está disponible en las siguientes presentaciones:

- Caja de 12 unidades por cuarto de galón.
- Caja de 6 unidades por galón.
- Garrafa de 5 galones.
- Tambores de 55 galones.
- Contenedores de 264 galones



**ROYAL Petroleum Corporation C.I S.A.S**

Zona Franca Industrial Km 1 vía Gaira. Planta 4F

Santa Marta, Colombia

Tel: (575) 4232258 – 3118109765

Email: [royal@royalpetroleum.co](mailto:royal@royalpetroleum.co)

[www.royalpetroleum.co](http://www.royalpetroleum.co)